



|   |                              |
|---|------------------------------|
| TdS: Art. 0895 <b>SPIAGGE (Classic e Gold Rev. 1.2 / Silver Rev. 1.1)</b> | Date of Update<br>08/05/2015 |
|---|------------------------------|

**Decorative water based finish that recall the sand and dunes of natural beaches. Mould resistant formula**

**CARATTERISTICHE:**

**SPIAGGE** is a decorative water based finish for interior surfaces with shiny reflections that recreate the sand and dunes of natura beaches. The precious pigments included in the product will reflect the light in the environment. Depending on the choosen colour, a greater or lower hiding power can be obtained. **SPIAGGE** is available in two bases, gold and silver, based on acrylic binder. Mould resistant formula

**CAMPI D'IMPIEGO:**

**SPIAGGE** can be used on walls and ceilings on: bricks, plaster, plasterboards, gypsum, old paints, wood, paper, cardboard, light alloys, plastic and metallic surfaces, after applying suitable primer.

**MODALITÀ DI APPLICAZIONE:**

Surfaces need to be clean, dry, solid and sound. Scrape off and brush any old paint or flaky parts. Remove any humidity, smoke or nicotine stains and isolate any humidity leakages. Sterilize any mould, fungi or algae contaminations with **MUROSANO RISANANTE**. Fill any crack and smooth uneven surfaces. Apply one coat of **SMARTCOAT EXTRATHIN 0,1 mm** white colour by brush or roller. On wood, plastic or metal surface apply appropriate primer. After 12 hours apply one or two coats of **SPIAGGE** by spalter brush crossing the strokes.

**RACCOMANDAZIONI:**

- Mix the product with care before use.
- Before application, ensure that the surface is perfectly dry and hardened, and that it has good adherence to the supporting ground. It must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence or any other defect that could impair adherence or successful results.
- Keep packages of paste products from freezing (minimum +5°C).
- Store product in a cool, dry place and do not expose to direct sunlight.
- Use product at a temperature of the work environment and treated surface between +8°C and +35°C. Relative humidity must not exceed 75%.
- Do not allow drying to take place with temperature of the work environment and treated surface below 5°C.
- Do not apply product if rain is likely or in the presence of strong sunlight, strong winds or persistent fog.
- In case of exterior application protect treated surfaces from rain for the time required to allow product to fully harden.
- Scaffolding should be erected in a way that allows work to be continued uninterrupted until a natural boundary of the building is reached, to avoid seams, overlaps and differences in shade.
- Obtain enough of the colour in a single batch to complete the job or at least to complete portions of work which do not draw attention to shade differences.
- Wash all equipment with water immediately after use.

**DATI TECNICI:**

|                        |   |
|------------------------|---|
| <b>COVERAGE</b>        | 5-6 m <sup>2</sup> /l per coat                              |
| <b>DILUTION</b>        | Ready to use  |
| <b>SPECIFIC WEIGHT</b> | 1,35 ± 0,05 kg/l  |
| <b>pH</b>              | 8 ± 1   |
| <b>STORAGE</b>         | In perfectly sealed packs, away from frost, up to 12 month. |
| <b>CONFEZIONI</b>      | 2,5 l – 1 l   |
| <b>COLOURS</b>         | Collezione "EVENTI"   |
| <b>BASES</b>           | Oro - Argento   |

**Classification according to D.Lgs n. 161 of 27.03.2006**

1) paint for decorative effects;  
Limit values VOC. in g/l: from 01.01.2010 = 200 g/l  
Max value VOC. in the product: 50 g/l of compound

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

**Colorificio MP S.r.l.**